

**OPTICAL MOLDED ARTICLE USING TRANSPARENT POLYESTER/  
POLYCARBONATE RESIN COMPOSITION AND RESIN COMPOSITION FOR  
PRODUCING THE MOLDED ARTICLE**

**Patent number:** JP9183892  
**Publication date:** 1997-07-15  
**Inventor:** ISAWA KENICHI; MORI KENICHI; NAGAI KOJI  
**Applicant:** GE PLASTICS JAPAN LTD  
**Classification:**  
**- international:** C08L67/02; C08K5/00; C08L69/00; G02B1/04  
**- european:**  
**Application number:** JP19950352370 19951228  
**Priority number(s):** JP19950352370 19951228

**Report a data error here**

**Abstract of JP9183892**

**PROBLEM TO BE SOLVED:** To obtain a molded article suitable for recording media such optical disks, reduced in optical strain and excellent in flowability during molding and impact strength by using a transparent polyester/polycarbonate resin composition each having a predetermined haze value and birefringence. **SOLUTION:** This polyester/polycarbonate resin composition comprising (A) 99-1 pts.wt. transparent polycarbonate and (B) 1-99 pts.wt. transparent polyester resin such as polyethylene terephthalate, polybutylene terephthalate, etc., each having  $\leq 1\%$  haze value within  $\pm 50\text{nm}$  birefringence, uniform glass transition temperature and mixed uniformly and containing (C) 0.05-50,000ppm (based on 100 pts. of sum total of the components A and B) ester interchange reaction catalyst (e.g. an alkali metal, etc.) and (D) 0.0001-1 pt.wt. protonic acid such as phenol, etc., is used for producing optical molded articles.

Data supplied from the esp@cenet database - Worldwide